

SSB HOSE

"Flexible Solutions for Today's Rigid Industries"



Phone: 905-755-9610
Toll Free: 877-755-9610
Fax: 905-755-9612
E-mail: sales@ssbhose.com

BRONZE TUBULAR BRAID

- Wide range of constructions including 24, 36, 48, and 72 carrier designs
- Clean and oil-free
- Engineered for optimal hose coverage
- Manufactured on hose mandrels to ensure proper braid angle

Bronze Tubular Braid for Series 400 Hose

Nominal Hose Size (in.)	Braid Construction	Braid I.D. (in.)	Braid Coverage (%)	Max. Working Pressure at 70°F (PSIG) ^a	Weight Per Foot (lb.)	Typical Mill Length (ft.)
1/4	24 x 5 x .014	0.46	94	934	0.100	30-100
3/8	24 x 7 x .014	0.61	97	704	0.130	30-100
1/2	24 x 8 x .014	0.75	95	566	0.150	30-100
3/4	36 x 8 x .014	1.04	95	468	0.220	30-100
1	36 x 5 x .020	1.34	80	334	0.270	30-100
1-1/4	48 x 6 x .020	1.78	91	306	0.440	30-60
1-1/2	48 x 7 x .020	2.09	88	297	0.540	30-60
2	48 x 8 x .020	2.54	85	210	0.620	30-60
2-1/2	72 x 8 x .020	3.33	90	194	0.980	30-60
3	72 x 10 x .020	3.89	95	166	1.200	30-60
4	72 x 12 x .020	4.79	95	145	1.460	30-50

a. Maximum working pressure shown is calculated for SSB Hose bronze hose and corresponding single layer bronze braid. See **Series HBA annular bronze hose** specifications for additional information.