

SSB HOSE

"Flexible Solutions for Today's Rigid Industries"



Phone: 905-755-9610
Toll Free: 877-755-9610
Fax: 905-755-9612
E-mail: sales@ssbhose.com

MONEL TUBULAR BRAID

- Wide range of constructions including 24, 36, 48, and 72 carrier designs
- Clean and oil-free
- Engineered for optimal hose coverage
- Manufactured on hose mandrels to ensure proper braid angle

Monel Tubular Braid for Series 500 Hose						
Nominal Hose Size (in.)	Braid Construction	Braid I.D. (in.)	Braid Coverage (%)	Max. Working Pressure at 70°F (PSIG) ^a	Weight Per Foot (lb.)	Typical Mill Length (ft.)
1/4	24 x 6 x .012	0.46	90	1701	0.075	30-100
3/8	24 x 8 x .012	0.61	94	1272	0.112	30-100
1/2	24 x 8 x .012	0.75	85	852	0.116	30-100
3/4	36 x 8 x .012	1.04	89	709	0.152	30-100
1	36 x 8 x .016	1.34	88	692	0.274	30-100
1-1/4	48 x 8 x .016	1.78	90	611	0.342	30-60
1-1/2	48 x 8 x .016	2.09	84	419	0.400	30-60
2	48 x 8 x .020	2.54	88	313	0.483	30-60
3	72 x 10 x .020	3.89	95	300	1.130	30-60
4	72 x 12 x .020	4.79	95	263	1.463	30-50

a. Maximum working pressure shown is calculated for SSB Hose monel hose and corresponding single layer Monel braid. See **Series HMA annular monel hose** specifications for additional information.